you can
Canon

Large Format Media
Product Information Document

1928B Glossy Photo Quality Paper 300 g/m²

Description
This top quality photo inkjet paper has a quality photo coating for high grade natural colour prints of graphic pictures, presentations and photos. The paper is instant dry, is smudge resistant and provides good colour density and excellent image sharpness. This paper is compatible with a large range of dye and pigment digital printing systems, and is the most ideal product for users who need top quality photographic re-productions.

Features
Extremely quick drying, dye and pigment ink compatible, good colour density, excellent image sharpness, smudge resistant, lamination not necessary, easy handling.

Applications
Photography, portraits, posters, graphic art reproductions, exhibition graphics, indoor and outdoor signage.

Available widths

Article number	Width (mm)	Length (m)	Order Multiple	Mercury Code
97003072	432	30	1	1928B001AA
97003073	610	30	1	1928B002AA
97003074	914	30	1	1928B003AA
97003075	1067	30	1	1928B004AA
97003076	1270	30	1	1928B005AA
97003077	1524	30	1	1928B006AA

Compatibility and profiles
Advised Driver / panel settings: HW Glossy Photo Paper / HW Gloss Photo
Refer for Onyx and other profiles to www.mediaguide.oce.com
Select your Canon printer to find matching media and media profiles.

Printing
For optimum results select the best possible print settings.

Lamination
To add surface protection from dirt, abrasion and gas-fading, lamination is recommended. Although ink drying is virtually immediate, it is still recommended to allow a waiting time of approximately 3 hours before lamination.
In order to prevent moisture ingress and paper splitting, lamination with a 5-6mm encapsulated edge is also recommended. Laminate must be evenly applied to the print in order to avoid curling. Both hot and cold lamination is possible.

Physical Properties

Weight	300 ±7 g/m²
Calliper	288 ±5 microns
Gloss	47 ± 5
Whiteness	120 CIE

Storage Conditions
Store paper only in original boxes, out of direct sunlight and under normal climatic conditions (23 °C, 50% RH) until ready to use. Allow material to adapt to room conditions before use. Papers can absorb moisture in humid conditions or lose moisture in low humidity conditions. Highly humid conditions make the ink drying time longer and this could interfere with proper laminate adhesion.

Shelf Life
2 years from shipping date when stored under ideal conditions (see above)